

## TECHNICAL DATA SHEET

# PRODUCT: FUTRFILL

DESCRIPTION/ DESCRIPTION : Filled TPE

<u>COMPOUND PROPERTIES</u>	<u>UNITS/</u>	<u>TEST METHOD /</u>	<u>VALUES (a)/</u>
SPECIFIC GRAVITY		ASTM D792	1.47 - 1.57
HARDNESS	Shore A	ASTM D2240	54 - 59
TENSILE STRENGTH	psi	ASTM D412 ( 500mm/min)	MIN.265
ELONGATION AT BREAK	%	ASTM D412 (500mm/min)	MIN.250
PELLETS COUNT	p/g	In house	120-150

(a) Values shown are averages and are not to be construed as products specifications. Ces données sont des valeurs moyennes mais ne constituent pas les spécifications du produit.

### **E29355VERT/GREEN**

**This product is an Elastomer which has a Styrene-Butylene copolymer base. It is environmentally safe and does not contain any carcinogenics.**

While the information herein is believed to be reliable, no guarantee is made as to its accuracy or completeness. The conditions of use, handling, storage, and disposal, and the suitability of the product for particular uses are beyond our control. Consequently, all risks involving the use of the product are assumed by the user. Target Technologies International Inc. expressly disclaim all warranties of every kind and nature, express or implied, including the warranties of merchantability and fitness for a particular purpose.