

# TTII PRO-MAX 37 TPE INFILL

## TECHNICAL DATA SHEET

*Basic properties: prime, virgin elastomer base with natural fillers. The non-toxic technology is heavy metal, BPA phthalate and vinyl free.*

**REUSABLE ■ RECYCLABLE ■ SUSTAINABLE**

Property	ASTM Test Method	Measure Unit	Result
Hardness	D2240	Shore A	52-55
Density	D792	g/cm <sup>3</sup>	1.45 - 1.51
Bulk Density	D1895B	lbs/ft <sup>3</sup>	46.8 +/- 3.3
Bulk Density	D1895B	g/cm <sup>3</sup>	0.75 +/- 0.05
Abrasion Resistance	D1044	mm <sup>3</sup>	520 +/- 50
Elongation at Break	D638	%	650 +/- 50
Flame Retardant Testing	E648	Class 1 rating	Passed

- Shape: Semi Ovoid
- UV Resistance: Excellent
- Colors Available: Green, brown, sandy beige and custom colors
- Recyclability: Excellent
- Elasticity: Excellent
- Resistance against yellowing: Excellent

The information provided above is based on similarities to other material or laboratory testing using the test methods indicated and is believed to represent nominal results of those tests. Because conditions under which this material may be processed, tested or used cannot be anticipated, no warranty is given either expressed or implied as to the accuracy or reproducibility of this information for the fitness of this material for any particular use. This material is sold with the express that the purchasers, processors or other users of this material have sole responsibility through performance of their own testing to determine the suitability of this material for any particular use.