

TTII ALL PRO CORK INFILL CHD 62

HIGH DENSITY CORK SPECIFICATION SHEET

- PRODUCT:** Granulated Cork 1/2 mm
- SCOPE:** Granulated Cork Physical Properties Description
- PRODUCTION DESCRIPTION:** Natural Cork Granule With Caliber 1/2 mm
- PHYSICAL PROPERTIES:**

CHARACTERISTICS	SPECIFICATION	NORM	
Bulk Density	160 - 200 kg/m ³	ISO 2031	
Moisture Content	< 12%	ISO 2190	
Size Analysis By Mechanical Sieving	ASTM Sieves (mm) % of Retention	ISO 2030	
	- 2.8		0%
	- 2		≤ 20%
	- 1.6		
	- 1		≥ 80%
	- 0.8		
	- 0.212		≤ 1%
	Under	0%	

MATERIAL INSPECTION PLAN: Quality Control Requirements

EQUIPMENT/OPERATION	PROPERTIES UNDER CONTROL		
	DENSITY (kg/m ³)	MOISTURE CONTENT(%)	GRANULE DISTRIBUTION (%)
Density Evaluation	Once Per Hour	Once Per Hour	Once Per 2 Hours
Lot Formation (bags from 35 kg)	Each 10 Bags	Each 10 Bags	Each 20 Bags
Lot Formation (bags from 75 kg)	Each 5 Bags	Each 5 Bags	Each 15 Bags

Bag Size	Quantity per Container
832 lbs	22 Bags / 18,302 lbs