

# SPECIFICATION SHEET

TTII® PLAYSAFE 65™ COLOR-COATED EPDM



1. Produced in USA
2. Base granule 100% EPDM virgin material
3. Contains no recycled materials
4. Urethane color-coated EPDM with antimicrobial option
5. Color coating is UV stabilized
6. Passes FIFA 2015 and World Rugby 2020 UVA 5000 hr testing
7. Passes Friability EN933-1, EN1097-3, EN15330-5
8. Lisport – no negative effects after 20,000 cycles
9. Passes heavy metal testing DIN 18035-7, F3188, EN71-3, ASTM F963Z, EPA6010
10. PAH Testing ASTM F3496
11. Phthalates Testing - internal method
12. Thermal Stability - no agglomeration at 110°C/230°F
13. Very little to no water absorption due to coating
14. Sulfur cured
15. Bulk density: 27 – 30 lbs per cubic ft
16. Dust free
17. Odorless
18. Not oily
19. 10-18 gradation
20. Standard colors available: green and tan
21. 10 year warranty on coating for sportsfields (ensuring 75%+ coverage on product)
22. 16 year warranty on coating for residential (ensuring 75%+ coverage on product)

Typical sieve specifications:

Sieve Size	Min	Max
10	0	5
12	20	30
16	55	70
18	5	20
20	0	5